

FloorShield Thermal Underfloor

Description

ecoinsulation® FloorShield Underfloor insulation with DriTherm® technology is made using a silicone treatment that is added to the glasswool during manufacture to upgrade the moisture resistance of the insulation, and provide guaranteed water resistance for 50 years.

ecoinsulation® FloorShield Underfloor insulation comes faced with a wind-wash barrier, which provides protection to air movement under the floor for enhanced thermal performance and is made using:

- Up to 80% recycled glass
- ECOSE® Technology - binder with no added formaldehyde
- TwinTech® - dual forming technique for a smooth finish on both sides.



Product Range

| Product code | R-Value (m ² K/W) | Thermal conductivity (W/mK) | Thickness (mm) | Width (mm) | Length (mm) | Area per pack (m ²) | Pieces per pack | Pack weight (kg) |
|--------------|------------------------------|-----------------------------|----------------|------------|-------------|---------------------------------|-----------------|------------------|
| 705170 | 2.6 | 0.036 | 90 | 420 | 1160 | 2.9 | 6 | 5.5 |

All dimensions are nominal.

Technical Data*

Water Vapour Absorption

- Less than 5% by weight.

Corrosion Resistance

- No greater than sterile cotton.

Microbial Growth

- Does not support microbial growth.

Fire Hazard Properties (AS/NZS 1530.3)

- Ignitability: 0, Spread of flame: 0.
- Heat Evolved: 0, Smoke Developed: 0-1.

Combustibility (AS 1530.1)

- Non-combustible.

Performance*

Thermal
AS/NZS 4859.1 (2018).

*The technical and performance data refers to the insulation material and does not include the facing.

FloorShield Thermal Underfloor


Suitable for sub-floor applications

ecoinsulation® FloorShield Underfloor batt is suitable for most sub-floor applications including pole houses and open sub-floors.

**Sub-floor with
timber battens**




Pole house *



**Sub-floor solid
perimeter**



Workshop spaces



Garage ceilings



Basement rooms



*sub-floors that are subjected to high winds may require a suitable lining material

FloorShield Thermal Underfloor

Specification Compliance

AS/NZS 4859.1 (2018) Materials used in the Thermal Insulation of Buildings **ecoinsulation**® glasswool will contribute to compliance with the Building Code of Australia (BCA) requirements.

ecoinsulation® glasswool is an acceptable solution in terms of the Australian Building Code. This product is designed for use in timber and metal frame applications in new and existing domestic and commercial buildings.

Bio-solubility

The formulation used for **ecoinsulation**® glasswool has been independently assessed to meet the requirements of the stringent Note Q standard (and is therefore consistent with the highest Australian and New Zealand industry standards), and also assessed by Knauf Insulation against the criteria of the Australian Safety and Compensation Council ASCC Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008 3rd Edition]. As a result of this assessment, **ecoinsulation**® glasswool is not classified as hazardous according to the NOHSC criteria.

Environmental

ecoinsulation® glasswool represents no known threat to the environment and has zero Ozone Depletion Potential and zero Global Warming Potential.

- GreenTag Level A certified.

Features and Benefits

Proven Performance

- Preferred by professional installers concerned with quality, appearance and productivity.
- Excellent acoustical properties reduce sound transmission in the home when properly installed in walls, ceiling and floor systems.
- Silicone treated glasswool - moisture resistant

Durability

- **ecoinsulation**® glasswool is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.
- DriTherm® technology - silicone treated for increased durability.

Superior Handling

- Highly resilient insulation recovers quickly to full thickness for a snug fit and superior finished aesthetics.
- Consistent quality materials that feel good, cut easily and can be installed fast.
- Low dust for easier handling and increased productivity.

Convenient Packaging, Easier Handling

- **ecoinsulation**® glasswool is packaged in a strong, white poly bag that offers excellent protection from abuse, dust and moisture.
- **ecoinsulation**® glasswool packages feature easy to follow installation instructions.
- MasterBag insulation units (containing multiple packs) ensure reduced handling costs with improved compression – more square metres per bag, more square metres per truck load, fewer trips to the job site and less warehouse space for storage.

Superior Service and Support

- We are focused on providing first class customer service, producing high quality products and 'in full on time' deliveries.
- We are committed to providing a comprehensive range of relevant sales and marketing literature and web-based technical information to support specifiers and customers.

ecoinsulation
glasswool



Eco Insulation Systems Ltd
PO Box 77-059
Mt Albert Auckland NZ 1025



www.ecoinsulation.co.nz



products@ecoinsulation.co.nz



0800 400 326