



ecotherm[®] Underfloor Insulation

ecotherm[®] Underfloor – Application

ecotherm[®] Underfloor is a 100% polyester insulation material able to be installed without the need for protective clothing or equipment. It is manufactured from thermally bonded polyester fibres to give a soft, fluffy, fleece-like material and is cut to fit between floor joists. **ecotherm[®] Underfloor** complies with the insulation standard AS/NZS 4859.1.

ecotherm[®] Underfloor – Identifying it

ecotherm[®] Underfloor polyester insulation is light blue in colour. Individual **ecotherm[®] Underfloor** packs are labelled to identify the specific R-Value, coverage per pack in m², material width, unit number or length of material, nominal thickness, minimum weight and date of manufacture in accordance with AS/NZS 4859.1.

ecotherm[®] Underfloor – Benefits and features

- User friendly and safe to install without protective clothing.
- Manufactured from a high percentage of recycled plastic (PET bottles).
- Recyclable at the end of its life.
- It will not slump or settle (50 year durability rating to NZBC B2), and it is not affected by moisture, mould or mildew.
- Non-irritant, non-allergenic, non-toxic and odourless.
- Naturally resistant to insect and vermin attack.

ecotherm[®] Underfloor – Environmental

ecotherm[®] Underfloor polyester insulation and its associated packaging is fully recyclable.

Eco Insulation is committed to the development and fostering of sustainable building products and practices and are members of the Sustainable Business Network and New Zealand Green Building Council.

ecotherm® Underfloor – Thermal performance

ecotherm® Underfloor is available in the specific R-Values given in Table 1. To obtain the installed R-Value of ecotherm® Underfloor insulation, refer to NZS 4218 or the BRANZ House Insulation Guide which takes account of the construction being used to give an R-Value for the completed element. Compliance with the requirements of NZBC H1 and E3 can then be determined.

ecotherm® Underfloor Polyester Thermal Insulation

	Insulation R-Value	AS/NZS 4859.1	Width (mm)	Thickness (mm)	Actual m ² Per Pack	Rolls Per Pack
Underfloor	1.5	✓	510	100	20	4
		✓	650	100	20	4
	1.8	✓	510	100	25	4
		✓	650	100	25	4

TABLE 1

ecotherm® Underfloor – Corrosion

ecotherm® Underfloor polyester insulation is no-corrosive to carbon steel when tested to NZS 4222, copper and aluminium.

ecotherm® Underfloor – Testing

The following independent testing of ecotherm® Underfloor insulation has been undertaken (copies of the test reports are available on request):

- Thermal resistance / **BRANZ**
- Corrosivity / **Materials Performance Technologies**

ecotherm® Underfloor – Finding out more

Eco Insulation will check and certify the installation of their products when their own licenced installers are used. Refer to our website for your nearest franchise. To obtain further information on ecotherm® Underfloor Insulation call toll free 0800 400 326.

Head Office

Eco Insulation Systems Ltd
PO Box 77-059
Mt Albert
Auckland 1350
technicalsupport@ecoinsulation.co.nz

0800 400 326

Local Stockist

ecoinsulation